

ODOR STOP

OPERATING INSTRUCTIONS – SAFETY - MAINTENANCE – SPECIFICATIONS

**This manual has important safety warnings and operating information.
Please read before using the unit and save for future reference.**

ODOR STOP will neutralize odor in a room up to 10,000 sq ft. Odorchem's 4L GEL Jar will last from 4 – 6 weeks, depending on temperature and humidity levels of the room, and the airflow setting of the ODOR STOP.

OPERATING INSTRUCTIONS

1. Operate the ODOR STOP on a level surface only. This will prevent GEL from entering the fan. Remove lid on 1 gal (4 liter) jar of ONA Gel. Screw the 4 L Gel container to the bottom of the ODOR STOP unit.
2. Plug the ODOR STOP into grounded 110/220V outlet and switch to "High" for maximum air flow of 225 cfm or adjust to suit the required amount of odor control.
3. When the GEL is reduced to within one inch of the bottom of the jar, replace the GEL jar. Stir GEL weekly to maintain proper evaporation rate.

SAFETY INFORMATION

The ODOR STOP is equipped with a three-terminal type grounding plug on the electrical cord. It must be plugged into a properly grounded three-prong outlet. The unit is designed to operate on ordinary household 110/120 volt, 60 Hertz alternating current.

- Never put the ODOR STOP into standing water due to shock hazard.
- Always operate the ODOR STOP in a horizontal position to prevent spillage and immersion of motor.
- Connect the power supply to an appropriate power source. Be sure that all electrical cords and extensions are of adequate size and properly insulated.
- Never allow the rear of the unit to become plugged with paper or other loose materials.
- Never place the ODOR STOP on dust, sand, or loose paper. Materials may become drawn up into the air intake while operating causing extreme damage to the motor.
- Never attempt any servicing or cleaning on the ODOR STOP while it is plugged into electrical current. This may result in shock or injury.
- Never probe the fan with wire or other instruments while the unit is operating.

MAINTENANCE

- The unit should be kept clean.
- Verify the level of GEL in the 4 L pail every week.

SPECIFICATIONS

Weight	6.6 kgs (14.5 lbs)
Ship weight	12 kgs (25 lbs)
Capacity of pail	4 Liters (1 gallons)
Output	225 Cubic feet per minute
Power consumption	Up to 42 watts
Power	110/220 Volts
Cycle	50/60 Hertz

ODOR NEUTRALIZATION

ODOR STOP is to be used ONLY with Odorchem's products. Odorchem's products do not merely mask odors but bonds with the offending molecules rendering them odorless. The active ingredients are a blend of 44 essential oils and plant-derived compounds, native to Australia and Asia. Odorchem's products neutralizes a wide spectrum of odors. Odorchem's products are safe and biodegradable, designed for use in any environment.

TO BE USED WITH ODORCHEM'S ONA GEL.

All Odorchem's products are scientifically engineered to be completely non-toxic and environmentally safe. They have proven to effectively neutralize virtually any odor permanently.

Some of the applications in which ODOR STOP has been successful neutralizing odors include:

Animal kennels	Hotel rooms	Refrigerated transport
Animal transport	Kitchens	Restaurants
Auditoriums	Laundry rooms	Slaughterhouses
Automobile repair shops	Locker rooms	Storage areas
Butcher shops	Motel rooms	Warehouses
Chicken sheds and farms	Nursing homes	Waste disposal areas
Clubs	Paint shops	Waste sludge storage areas
Designated smoking areas	Pig farms	Waste storage areas
Dog kennels	Poultry farms	Waste transfer station
Drains	Public bathrooms	Yeast production plants
Fish markets	Pubs & Bars	
Food processing plants		
Funeral homes		
Greenhouses		
Gyms		